



Model code : ISM2005D-<N1>T-<N2><F><L><W>-FC/SC-24/48w

	ISM2005D	N1	N2	F	L	W	FC/SC	24/48w
Nomenclature	Code		No. of	No. of	Optical fibre type: M: Multi-mode dual-fibre S:	Transmit/receive wavelength: distance: 3:Tx1310/R x1310nm	Connector type:	Power supply voltage
	Description	Subseries	T(X) ports	of FX ports	Single-mode (Multimode dual-fibre B: Single-mode single-fibre	20/40/60/80 /120 5:Tx1550/R x1550nm 53:Tx1550/R x1310nm 2KM, default is omitted.) 35:Tx1310/R x1550nm	FC, SC optional	24VDC (18~36VDC) /48VDC (36~72VDC) optional

Example ISM2005D-3T-2M3-FC-24 ISM2005D-3T-2S203-SC-24 ISM2005D-5T-24

	T(X) port	3T	5T	
	Optional port combinations (i.e. <N1>T-<N2><F><L><W>-section)		No. of FX ports : 2	No. of FX ports : 0
		2M3	-	
		2S203	-	
FX port			2S205	-
			2S403	-
			2S405	-
			2S603	-

		2S605	-
		2S803	-
		2S805	-
		2B2053	-
		2B2035	-
		2B4053	-
		2B4035	-
		2B6053	-
		2B6035	-