



**Model code : ISM2008D-<N1>T-<N2><F><L><W>-FC/SC-24/48w**

		ISM2008D	N1	N2	F	L	W	FC/SC	24/48w
<b>Nomenclature</b>	<b>Code</b>		No. of	No. of	Optical fibre type:	Transmission distance:	Transmit/receive wavelength:	Connctor type:	Power supply voltage
	<b>Description</b>	Subseries	T(X) ports	FX ports	M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	x1310nm x1550nm 53:Tx1550/R x1310nm 35:Tx1310/R x1550nm	FC、SC optional	( 18~36V DC ) /48VDC ( 18~72V DC ) optional
<b>Example</b>		ISM2008D-6T-2M3-FC-24 ISM2008D-6T-2B2053-SC-24 ISM2008D-8T-24							

		T(X) port	6T	8T
		<b>Optional port combinations</b> (i.e. <N1>T-<N2><F><L><W>-section )		
	2M3			-
	2S203			-
<b>FX port</b>	2S205			-
	2S403			-
	2S405			-
	2S603			-

		2S605	-
		2S803	-
		2S805	-
		2B2053	-
		2B2035	-
		2B4053	-
		2B4035	-
		2B6053	-
		2B6035	-