



Model code : ISM2009D-<N1>T-<N2><F><L><W>-FC/SC-24/48w

		ISM2009D	N1	N2	N3	F	L	W	FC/SC	24/48w
Nomenclature	Code									
	Description	Subseries	No. of T(X) ports	No. of type-I FX ports	No. of type-II FX ports	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connctor type: FC、 SC optional	Power supply voltage 24VDC (18~36V DC) /48VDC (36~72V DC) optional
Example		ISM2008D-6T-2M3-FC-24 ISM2008D-6T-2B2053-SC-24 ISM2009D-9T-24								
Optional port combinations (i.e.<N1>T-<N2><F><L><W>-<N3><F><L><W>section)			T(X) port		6T			9T		
					Type-I FX ports : 3	Type-I FX ports : 2		Type-I FX ports : 3		
					Type-II FX ports : 0	Type-II FX ports : 1		Type-II FX ports : 0		
			FX port		3M3	2S203-M3		-		
					3S203	2S205-M3		-		
					3S205	2S403-M3		-		
		3S403	2S405-M3		-					



		3S405	2S603-M3	-
		3S603	2S605-M3	-
		3S605	2S803-M3	-
		3S803	2S805-M3	-
		3S805	2B2053-M3	-
		3B2053	2B2035-M3	-
		3B2035	2B4053-M3	-
		3B4053	2B4035-M3	-
		3B4035	2B6053-M3	-
		3B6053	2B6035-M3	-
		3B6035		-