

Model code : ISM3010D-<N1>T-2GSFP-<N2><F><L><W>-FC/SC-24/48w

	ISM3010D	N1	2GSFP	N2	N3	F	L	W	FC/SC	24/48w	
Nomenclature	Code	Subseries	No.of:2	T(X) Gigabit SFP ports	No. of type-I FX ports	No. of type-II FX ports	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80/120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connctor type: FC、SC optional	Power supply voltage 24VDC (18~36 VDC) /48VDC (36~72 VDC) optional
	Description										
Example	ISM3010D-6T-2GSFP-2M3-FC-24 ISM3010D-8T-2GSFP-24										
Optional port combinations (i.e.<N1>T-2GSFP-<N2><F><L><W>-<N3><F><L><W>section)	T(X) port			6T				8T			
				No. of FX ports : 2				No. of FX ports : 0			
				2M3				-			
	FX port			2S203				-			
				2S205				-			
			2S403				-				

		2S405	-
		2S603	-
		2S605	-
		2S803	-
		2S805	-
		2B2053	-
		2B2035	-
		2B4053	-
		2B4035	-
		2B6053	-
		2B6035	-