

Model code : ISE2008D-<N1>T-<N2><F><L><W>-FC/SC-24

Model code : ISE2008D-<N1>T-<N2><F><L><W>-FC/SC-24										
Nomenclature	Code Description	ISE1008D	N1	N2	F	L	W	FC/SC	24	
		Subseries	No. of T(X) ports	No. of FX ports	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80/120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connctortype: FC、SC optional	Power supply voltage 24VDC (12~48VDC)	
Example		ISE1008D-6T-2S805-FC-24			ISE1008D-7T-M3-SC-24		ISE1008D-8T-24			
Optional port combinations (i.e.<N1>T- <N2><F><L><W>-<N3><F><L><W>section)	T(X) port	6T			7T			8T		
		No. of T(X) ports : 2			No. of T(X) ports : 1			No. of T(X) ports : 0		
	FX port	2M3			M3			-		
		2B2053			B2053			-		
		2B2035			B2035			-		
		2B4053			B4053			-		
		2B4035			B4035			-		
		2B6053			B6053			-		
		2B6035			B6035			-		
		2S203			S203			-		
		2S205			S205			-		
		2S403			S403			-		
		2S405			S405			-		
		2S603			S603			-		
		2S605			S605			-		
		2S803			S803			-		
2S805			S805			-				