

Model code : ISE2005D-<N1>T-<N2><F><L><W>-FC/SC-24

		ISE2005D	N1	N2	F	L	W	FC/SC	24
Nomenclature	Code								
	Description	Subseries	No. of T(X) ports	No. of FX ports	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connctortype: FC、 SC optional	Power supply voltage 24VDC (12~48 VDC)
	Example	ISE2005D-4T-M3-FC-24 ISE2005D-4T-S203-SC-24 ISE2005D-5T-24							
Optional port combinations				T(X) port		4T		5T	
(i.e.<N1>T- <N2><F> <L><W>-				FX port		No.of T(X) ports : 1		No.of T(X) ports : 0	

<N3><F><L><W>section)	M3	-
	S203	-
	S205	-
	S403	-
	S405	-
	S603	-
	S605	-
	S803	-
	S805	-
	B2053	-
	B2035	-
	B4053	-
	B4035	-
	B6053	-
	B6035	-