

Model code : ISE2016D-<N1>T-<N2><F><L><W>-FC/SC-24

		ISE2016	N1	N2	F	L	W	FC/SC	24
		D							
Nomenclature	Code								
	Description	Subseries: D	No. of T(X) ports: T(X)	No. of FX ports: FX	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80/120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connctortype: FC, SC optional	Power supply voltage 24VDC (12~36VDC)
Example		ISE2016D-14T-2M3-FC-24			ISE2016D-14T-2S203-SC-24		ISE2016D-16T-24		
Optional port combinations (i.e.<N1>T- <N2><F><L><W>-<N3><F><L><W>section)				T(X) port		14T		16T	
						No.of T(X) ports : 2		No.of T(X) ports : 0	
						2M3		-	
						2S203		-	
						2S205		-	
						2S403		-	
				FX port		2S405		-	

	2S603	-
	2S605	-
	2S803	-
	2S805	-
	2B2053	-
	2B2035	-
	2B4053	-
	2B4035	-
	2B6053	-
	2B6035	-