

Model code : ISE3008D-<N1>T-1GSFP-<N2><F><L><W>-FC/SC-24

Model code : ISE3008D-<N1>T-1GSFP-<N2><F><L><W>-FC/SC-24											
		ISE3008D	N1	GSFP	N2	N3	F	L	W	FC/SC	24
Nomenclature	Code	Subseries	No. of T(X) ports	Gigabit SFP	No. of type-I FX ports	No. of type-II FX ports	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connector type: FC、SC optional	Power supply voltage 24VDC (12~36VDC)
	Description										
Example		ISE3008D-4T-1GSFP-3B6035-FC-24 ISE3008D-4T-1GSFP-2S203-M3-SC-24									
Optional port combinations (i.e.<N1>T-1GSFP-<N2><F><L><W>-<N3><F><L><W>section)				T(X) port		4T					
				FX port		Type-I FX port : 3			Type-I FX port : 2		
						Type-II FX port : 0			Type-II FX port : 1		
						3M3			2S203-M3		
						3S203			2S205-M3		
						3S205			2S403-M3		
3S403			2S405-M3								

		3S405	2S603-M3
		3S603	2S605-M3
		3S605	2S803-M3
		3S803	2S805-M3
		3S805	2B2053-M3
		3B2053	2B2035-M3
		3B2035	2B4053-M3
		3B4053	2B4035-M3
		3B4035	2B6053-M3
		3B6053	2B6035-M3
		3B6035	