

**Model code : ISE3010D-<N1>T-2GSFP-<N2><F><L><W>-FC/SC-24**

		ISE3010D	N1	GSFP	N2	N3	F	L	W	FC/SC	24
<b>Nomenclature</b>	<b>Code</b>										
	<b>Description</b>	Subseries	No. of T(X) ports	Gigabit SFP	No. of type-I FX ports	No. of type-II FX ports	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connector type: FC、SC optional	Power supply voltage ( 12~36 VDC )
	<b>Example</b>	ISE3010D-4T-2GSFP-4B6035-FC-24 ISE3010D-4T-2GSFP-2S203-2M3-SC-24									
<b>Optional port combinations</b> (i.e.<N1>T-2GSFP-<N2><F><L><W>-<N3><F><L><W>section )				<b>T(X) port</b>		<b>4T</b>				<b>8T</b>	
				<b>FX port</b>		Type-I FX port : 4 Type-II FX port : 0		Type-I FX port : 2 Type-II FX port : 2		FX port : 0	
						4M3		2S203-2M3		-	

	4S203	2S205-2M3	-
	4S205	2S403-2M3	-
	4S403	2S405-2M3	-
	4S405	2S603-2M3	-
	4S603	2S605-2M3	-
	4S605	2S803-2M3	-
	4S803	2S805-2M3	-
	4S805	2B2053-2M3	-
	4B2053	2B2035-2M3	-
	4B2035	2B4053-2M3	-
	4B4053	2B4035-2M3	-
	4B4035	2B6053-2M3	-
	4B6053	2B6035-2M3	-
	4B6035		-