

**Model code : ISF2005E-<N1>T-<N2><F><L><W>-FC/SC-24**

Model code : ISF2005E-<N1>T-<N2><F><L><W>-FC/SC-24									
		ISF2005E	N1	N2	F	L	W	FC/SC	24
<b>Nomenclature</b>	<b>Code</b>		No. of	No. of	Optical fibre type:	Transmission distance:	Transmit/receive wavelength:	Connctor	Power supply
	<b>Description</b>	Subseries	T(X) ports	FX ports	M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	20/40/60/80/120 (Multimode distance is 2KM, default is omitted.)	3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 35:Tx1310/Rx1550nm	FC、SC optional	voltage 24VDC ( 5~32VDC )
<b>Example</b>		ISF2005E-3T-2M3-FC-24 ISF2005E-3T-2S203-SC-24							
<b>Optional port combinations</b> (i.e. <N1>T-<N2><F><L><W>-section )					<b>T(X) port</b>		3T		
					<b>FX port</b>		No. of FX ports : 2		
							2M3		
							2S203		
							2S205		
							2S403		
							2S405		

		2S603
		2S605
		2S803
		2S805
		2B2053
		2B2035
		2B4053
		2B4035
		2B6053
		2B6035