

Model code : ISF3010D-<N1>T-2GSFP-<N2><F><L><W>-FC/SC-24

	ISF3010D	N1	GSFP	N2	N3	F	L	W	FC/SC	24	
Code											
Nomenclature	Description	Subseries	No. of T(X) ports	Gigabit SFP	type-I FX ports	type-II FX ports	Optical fibre type:	Transmission distance:	Transmit/receive wavelength:	Connector type:	Power supply voltage
							M: Multi-mode dual-fibre	20/40/60/80/120 (Multimode distance is 2KM, default is omitted.)	3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	FC, SC optional	(12~36 VDC)

Example ISE3010D-4T-2GSFP-4B6035-FC-24 ISE3010D-4T-2GSFP-2S203-2M3-SC-24 ISF3010D-8T-2GSFP-24

Optional port combinations (i.e.<N1>T-2GSFP-<N2><F><L><W>-<N3><F><L><W>section)	T(X) port	4T		8T
			Type-I FX port : 4	Type-I FX port : 2
		Type-II FX port : 0	Type-II FX port : 2	Type-II FX port : 0
		4M3	2S203-2M3	-
		4S203	2S205-2M3	-
		4S205	2S403-2M3	-
		4S403	2S405-2M3	-



	4S405	2S603-2M3	-
	4S603	2S605-2M3	-
	4S605	2S803-2M3	-
	4S803	2S805-2M3	-
	4S805	2B2053-2M3	-
	4B2053	2B2035-2M3	-
	4B2035	2B4053-2M3	-
	4B4053	2B4035-2M3	-
	4B4035	2B6053-2M3	-
	4B6053	2B6035-2M3	-
	4B6035		-