

Model code : ISF3018D-<N1>T-2GSFP-<N2><F><L><W>-FC/SC-24

		ISF3018D	N1	N2	F	L	W	FC/SC	24
Nomenclature	Code		No. of	No. of	Optical fibre type:		Transmit/receive		
	Description	Subseries	T(X) ports	FX ports	M: Multi-mode dual-fibre	distance: 20/40/60/80 /120 (Multimode)	3:Tx1310/R x1310nm	Connector type: FC、SC	Power supply voltage (12~36 VDC)
					S: Single-mode dual-fibre	distance is 2KM, default is omitted.)	5:Tx1550/R x1550nm	optional	
					B: Single-mode single-fibre		35:Tx1310/R x1550nm		
	Example	ISE3018D-14T-2GSFP-2M3-FC-24 ISE3018D-14T-2GSFP-2S203-SC-24 ISF3018D-16T-2GSFP-24							
Optional port combinations (i.e.<N1>T-2GSFP-<N2><F><L><W>-section)				T(X) port		14T		16T	
						No. of FX ports : 2		No. of FX ports : 0	
						2M3		-	
				FX port		2S203		-	
						2S205		-	
						2S403		-	

		2S405	-
		2S603	-
		2S605	-
		2S803	-
		2S805	-
		2B2053	-
		2B2035	-
		2B4053	-
		2B4035	-
		2B6053	-
		2B6035	-